

Tirrap Plástico

COD: 07011019



Descripción del producto

| | |
|---|--|
| Material | Polyamide 6.6 |
| Material Brand | China Huafeng158L;Radici A45L;Invista 4820L |
| Flammability Of Raw Material | UL 94 - V2 |
| Humidity Absorption | 2,7%-2,8% (23°C -50% R.H.) |
| Installation Temperature | -10°C ~+85°C |
| Working Temperature | -40°C ~+85°C |
| Max Sustaiable Tempeature For Short Time | +110°C |
| Feature | <p>Good resistance to bases, oils, greases, oil derivates,chloride solvents. Limited resistance to acids.</p> <p>Not resistant to phenols.</p> <p>Carbon black addition gives a better UV resistance (only for Black Cabe Ties)</p> |
| Usage | <p>First, the cable is bundled in the nylon cable tie;</p> <p>Next,the tail of the nylon cable tie is clamped by the tool;</p> <p>Finally, tighten with tool, The cable tie gun can fix the wire harness at the same time and cut off the belt body</p> <p>Releasable cable ties offer the perfect solution for those applications requiring reuse or reinstallation of a cable tie.</p> |
| Application | Used to bundle cables, wires, conducts, plants or other things in the industry of electrical & electronic, lighting, hardware, pharmaceutical, chemical, computer, machinery, agriculture, etc. |
| Delivery time | 7-15 days (Depend on your order quantity) after confirm order. |

